



Socay 8KP Series TVS Diode 8KP78CA Axial Lead Transient Voltage Suppressor 8000W

Our Product Introduction

Basic Information

- Place of Origin: Shenzhen, Guangdong, China
- Brand Name: SOCAY
- Certification: UL, REACH, RoHS, ISO
- Model Number: 8KP78CA
- Minimum Order Quantity: 250PCS
- Price: Negotiable
- Delivery Time: 5-8 work days



Product Specification

- Product Name: TVS Diodes
- Package Type: R6/P600
- Vrwm: 78.0V
- Vbr@It (Min.): 86.7V
- Vbr@It (Max.): 95.8V
- It: 5mA
- Vc@Ipp: 126.0V
- Ipp: 64.3A
- Ir@Vrwm: 5μA

for more products please visit us on socaydiode.com

Product Description

Socay 8KP Series TVS Diode 8KP78CA Axial Lead Transient Voltage Suppressor 8000W

DATASHEET: [8KP Series_v2309.1.pdf](#)

8KP78CA Description:

The 8KP series is especially designed to safeguard sensitive electronic components from voltage transients induced by lightning and other transient voltage events.

Part Number		Reverse Stand-Off Voltage V_{RWM} (V)	Breakdown Voltage V_{BR} (V) @ I_T		Test Current I_T (mA)	Maximum Clamping Voltage V_C (V) @ I_{PP}	Maximum Peak Pulse Current I_{PP} (A)	Maximum Reverse Leakage I_R (μA) @ V_{RWM}
Uni	Bi		MIN	MAX				
8KP18A	8KP18CA	18	20.0	22.1	5	29.2	273.9	5
8KP20A	8KP20CA	20	22.2	24.5	5	32.4	246.9	5
8KP22A	8KP22CA	22	24.4	26.9	5	35.5	225	5
8KP24A	8KP24CA	24	26.7	29.5	5	38.9	206	5
8KP30A	8KP30CA	30	33.3	36.8	5	48.4	165	5
8KP33A	8KP33CA	33	36.7	40.6	5	53.3	150	5
8KP36A	8KP36CA	36	40.0	44.2	5	58.1	148	5
8KP40A	8KP40CA	40	44.4	49.1	5	64.5	124	5
8KP43A	8KP43CA	43	47.8	52.8	5	69.4	115	5
8KP45A	8KP45CA	45	50.0	55.3	5	72.7	110	5
8KP48A	8KP48CA	48	53.3	58.9	5	77.4	103.4	5
8KP51A	8KP51CA	51	56.7	62.7	5	82.4	97.1	5
8KP58A	8KP58CA	58	64.4	71.2	5	93.6	86.5	5
8KP60A	8KP60CA	60	66.7	73.7	5	96.8	83.7	5
8KP64A	8KP64CA	64	71.1	78.6	5	103.0	78.6	5
8KP70A	8KP70CA	70	77.8	86.0	5	113.0	71.7	5
8KP75A	8KP75CA	75	83.3	92.1	5	121.0	66.9	5
8KP78A	8KP78CA	78	86.7	95.8	5	126.0	64.3	5

8KP78CA Features:


- u Low leakage
- u Uni and Bidirectional unit
- u P600 package glass passivated junction
- u Excellent clamping capacity
- u 8000W Peak power capability with a $10 \times 1000\mu s$ waveform Repetition rate (duty cycle): 0.01% Duty cycle
- u Fast response time
- u RoHS compliant

8KP78CA Applications:



TVS devices are ideal for protecting I/O interfaces, VCC buses and other sensitive circuits used in telecoms, computing, industrial and consumer electronics applications.

Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation with a 10/1000 μs waveform (Fig.1)(Note 1), (Note 2)	P_{PPM}	8000	Watts
Peak Pulse Current with a 10/1000 μs waveform.(Note1, Fig.3)	I_{PP}	See Next Table	Amps
Power Dissipation on Infinite Heat Sink at $T_L=75^\circ C$	$P_{M(AV)}$	8.0	Watt
Peak Forward Surge Current, 8.3ms Single Half Sine Wave (Note 3)	I_{FSM}	500	Amps
Operating junction and Storage Temperature Range.	T_J, T_{STG}	-55 to +150	$^\circ C$

Functional Diagram



I-V Curve Characteristics




Physical Specifications

Weight	0.007 ounce, 0.21 gram
Case	JEDEC DO-214AB Molded Plastic over glass passivated junction
Polarity	Color band denotes cathode except Bipolar
Terminal	Matte Tin-plated leads, Solderable per JESD22-B102D

Environmental Specifications


Temperature Cycle	JESD22-A104
Pressure Cooker	JESD22-A102
High Temp. Storage	JESD22-A103
HTRB	JESD22-A108
Thermal Shock	JESD22-A106

Soldering Parameters




Reflow Condition		Lead-free assembly
Pre Heat	-Temperature Min ($T_{s(min)}$)	150°C
	-Temperature Max ($T_{s(max)}$)	200°C
	-Time (min to max) (T_s)	60 - 180 Seconds
Average ramp up rate (Liquidus Temp T_L) to peak		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	-Temperature (T_L) (Liquidus)	217°C
	-Time (min to max) (T_L)	60 - 150 Seconds
Peak Temperature (T_P)		260 +0/-5°C
Time within 5 °C of actual peak Temperature (t_p)		20 - 40 Seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max
Do not exceed		280°C

Dimensions




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	1.000	-	25.40	-
B	0.340	0.360	8.64	9.14
C	0.048	0.052	1.22	1.32
D	0.340	0.360	8.64	9.14

Part Numbering



Part Marking



Packaging			
Part Number	Component Package	Quantity	Packaging Option
8KP Series	R6/P600	250 PCS	Box

Packaging Dimensions	Unit: Inches (Millimeters)
----------------------	----------------------------

SOCAY owns the rights to a number of patents, trademarks, copyrights, trade secrets and other intellectual property.

SOCAY reserves the right to make changes to the products described herein without notice.

SOCAY makes no warranties, representations or guarantees as to the suitability of its products for any particular purpose and disclaims all liability.

The parameters listed in the SOCAY data sheet specification may vary from application to application, and actual performance may vary over time. All operating parameters must be verified by the customer's technical expert prior to application.

All responsibility and liability is disclaimed if any item in this warning is not followed.

 **SOCAY® Shenzhen Socay Electronics Co., Ltd.**

 +8618126201429

 sylvia@socay.com

 socaydiode.com

4/F, Block C, HeHengXing Science & Technology Park, 19 MinQing Road, LongHua District, Shenzhen City, Guangdong Province, China