


Transient Voltage Suppressors for ESD Protection

Low Capacitance
SE05D3V01GY

Features


- ◆ Protects one bi-directional I/O line
- ◆ Low clamping voltage
- ◆ Working voltage: 5V
- ◆ Low leakage current
- ◆ RoHS compliant
- ◆ IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- ◆ IEC61000-4-4 (EFT) 40A (5/50ns)
- ◆ IEC61000-4-5 (Lightning) 35A(8/20 μs)

SOD-323


Applications

- ◆ Cell phone handsets and accessories
- ◆ Microprocessor based equipment
- ◆ Personal digital assistants (PDA's)
- ◆ Notebooks, desktops, and servers
- ◆ Portable instrumentation

Pin Configuration



Mechanical Characteristics

- ◆ SOD-323 Package
- ◆ Molding compound flammability rating: UL 94V-0
- ◆ Quantity per reel: 3,000pcs
- ◆ Lead finish: lead free
- ◆ Reel size: 7 inch

Absolute Maximum Ratings (TA=25°C unless otherwise specified)

Parameter	Symbol	Value	Units
Peak Pulse Current ($t_P = 8/20\mu\text{s}$)	I_{PP}	35	A
Lead Solering Temperature	T_L	260 (10 sec.)	°C
Operating Junction Temperature Range	T_J	-55 ~ +125	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Transient Voltage Suppressors for ESD Protection

Low Capacitance

SE05D3V01GY

Electrical Characteristics (@ $T_A=25^\circ\text{C}$)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Reverse Working Voltage	V_{RWM}	--	--	--	5.0	V
Reverse Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	5.5	--	--	V
Reverse Leakage Current	I_R	$V_{RWM} = 5\text{V}$	--	--	1.0	μA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, $t_P = 8/20\mu\text{s}$	--	7	--	V
		$I_{PP} = 35\text{A}$, $t_P = 8/20\mu\text{s}$	--	12.5	--	V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$	--	75	--	pF

Ratings and V-I Characteristics Curves ($T_A=25^\circ\text{C}$, unless otherwise noted)

Fig. 1 V-I Curve Characteristics (Bi-directional)




Fig.2 Pulse Waveform (8/20 μs)




Fig. 3 Pulse Derating Curve






Fig. 4 ESD Clamping (30kV Contact)



SOD-323 Package Outline Dimensions


Symbol	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.60	1.70	1.80	0.063	0.067	0.071
B	0.25	0.32	0.40	0.010	0.013	0.016
C	2.30	2.60	2.80	0.091	0.102	0.110
D	0.80	0.95	1.10	0.031	0.037	0.043
E	1.20	1.30	1.40	0.047	0.051	0.055
F	0.08	0.13	0.18	0.003	0.005	0.007
L	0.475 REF			0.019REF		
L1	0.25	0.33	0.40	0.010	0.013	0.016
H	0.00	0.06	0.14	0.000	0.002	0.006

Warning


- ◆ SOCAY owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property.
- ◆ SOCAY reserves the right to make changes without further notice to any products herein.
- ◆ SOCAY makes no warranties, representations or warranties as to the fitness of its products for any particular purpose, and disclaims any liability.
- ◆ The parameters provided in the SOCAY datasheet specification may vary from application to application, and the actual performance may vary over time. All operating parameters must be verified by the customer's technical expert before application.
- ◆ Any and all responsibilities and liabilities are disclaimed if any item under this notice of warning is not complied with.