

Surface Mount Resettable PTCs


SCF260-0805RZC

Features

- u Resettable over current and over temperature protection
- u Small size of 0805
- u Fast time-to-trip
- u Small footprint
- u RoHS complaint
- u Low resistance

Applications

- u Computer
- u Industrial controls
- u Multimedia
- u Battery
- u Automotive
- u Game machines
- u Mobile phones
- u Portable electronics
- u Telephony and broadband



Electrical Parameters

Part Number	Hold Current	Trip Current	Rated Voltage	Max Current	Typical Power	Maximum Time To T _{rip}		Resistance	
	I _{hold} (A)	I _{trip} (A)	V _{max} (Vdc)	I _{max} (A)	P _{dtyp.} (W)	Current (A)	Time (Sec.)	R _{min} (Ω)	R _{1max} (Ω)
SCF260-0805RZC	2.6	5.2	6.0	50	1.0	12.0	5.0	0.003	0.035

I_{hold}= Hold current: maximum current at which the device will not trip at 25°C still air reflow soldering of 260°C for 20 sec.

I_{trip}= Trip current: minimum current at which the device will always trip at 25°C still air reflow soldering of 260°C for 20 sec.

V_{max}= Maximum continuous voltage device can withstand without damage at rated current.

I_{max}= Maximum fault current device can withstand without damage at rated voltage.

T_{trip}=Maximum time to trip(s) at assigned current reflow soldering of 260°C for 20 sec.

P_{dtyp.}= Typical power dissipation: typical amount of power dissipated by the device when in state air environment.

R_{min}= Minimum resistance of device in initial (un-soldered) state.

R_{max}=Maximum resistance of device in initial (un-soldered) state.

R_{1max}= Maximum resistance of device at 25°C measured one hour after reflow soldering of 260°C for 20 sec.

Value specified is determined by using the PWB with 0.030 " *1.5oz copper traces.

Caution: Operation beyond the specified rating may result in damage and possible arcing and flame.

Thermal Derating (Hold Current (A) at Ambient Temperature (°C))

Model	Maximum Ambient Operating Temperature (°C)							
	-40	-20	0	25	40	50	60	70
SCF260-0805RZC	3.9	3.4	2.9	2.6	2.3	1.8	1.7	1.6


Surface Mount Resettable PTCs

SCF260-0805RZC

Environmental Specifications

Test Item	Test Conditions	Accept / Reject Criteria
Recommended Storage Conditions	40°C max, 70% R.H. max	No Change
Passive Aging	85°C, 1000 hours	$\leq R_{1max}$
Moisture Resistance	85% RH, 85°C, 1000hrs	$\leq R_{1max}$
Thermal Shock	MIL-STD-202 Method 107G +85°C / -40°C 20 times	$\leq R_{1max}$
Vibration	MIL-STD-883C, Method 2007.1, Condition A	No Change
Solvent Resistance	MIL-STD-202, Method 215	No Change
Moisture Level Sensitivity	Level 1, J-STD-020C	No Change

Solder Reflow Recommendation



Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (T_S max to T_P)	1-3°C/second
Preheat : Temperature Min (T_{Smin}) Temperature Max (T_{Smax}) Time (T_{Smin} to T_{Smax})	150°C 200°C 60-180 seconds
Time maintained above: Temperature(T_L) Time (T_L)	217°C 60-150 seconds
Peak/Classification Temperature(T_P):	260°C
Time within 5°C of actual peak: Temperature	20-40 seconds
Ramp-down Rate:	6°C/ second max.
Time 25°C to Peak Temperature	8 minutes max.


Recommended reflow methods: IR, hot air oven, nitrogen oven. Devices can be cleaned using standard industry methods and solvents.

Note:

If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

Caution: Operation beyond the rated voltage or current may result in rupture electrical arcing or flame.


Part Numbering



Surface Mount Resettable PTCs

SCF260-0805RZC

Product Dimensions (Unit: mm)



Part Number	A		B		C		D		E	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
SCF260-0805RZC	--	2.50	--	1.80	--	1.00	0.20	--	0.10	--

Packaging Quantity

Part Number	Packaging Option	Quantity
SCF260-0805RZC	Tape & Reel	4000 PCS

Warning



- Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.
- PPTC device are intended for occasional over-current protection. Application for repeated over-current condition and/or prolonged trip are not anticipated.
- Avoid contact of PPTC device with chemical solvent. Prolonged contact will damage the device performance.